



Network Video Recorder

NVR-3326

3000
IP SERIES




Brief

- Video and audio channels: 26
- Supported protocols: ONVIF, RTSP
- Recording speed up to 780 fps at 1280 x 720
- Supports resolution up to 1920 x 1080
- Recorded stream size: 128 Mb/s in total from all cameras
- Internal HDDs mount: 2
- Monitor outputs: 3 (HDMI, VGA, BNC)

Software



Functions



VIDEO

IP Cameras	26 channels at 1280 x 720 resolution (video + audio)
Supported Cameras/Protocols	NOVUS, ONVIF, RTSP
Supported Resolution	max. 1920 x 1080
Compression	H.264
Monitor Output	main (split screen, full screen, sequence): 1 x HDMI, 1 x VGA, 1 x BNC (up to 3 monitors simultaneously)
Dualstreaming Support	yes*

AUDIO

Audio Output	1 x line-out (BNC)
--------------	--------------------

RECORDING

Recording Speed	780 fps (26 x 30 fps for 1280 x 720) 480 fps (16 x 30 fps for 1920 x 1080)
Stream Size	128 Mb/s in total from all cameras
Recording Mode	time-lapse, triggered by: REC/PANIC button, alarm input, motion detection
Schedule	individual settings for: each camera, each day of the week, configuration with an accuracy of: 1 min, possibility of combining individual recording modes
Prealarm/Postalarm	up to 96 MB/do 300 s

DISPLAY

Display Speed	780 fps (26 x 30 fps)**/**
PLAYBACK	
Playback Speed	390 fps (13 x 30 fps for 1280 x 720) 180 fps (6 x 30 fps for 1920 x 1080)
Recorded Data Search	by date/time
BACKUP	
Backup Methods	USB port (HDD or Flash memory), network
Backup File Format	AVI, DAV
STORAGE	
Internal storage for recording	available mount: 2 x HDD 3.5" 4 TB SATA
Total Capacity	8 TB
ALARM	
Internal Alarm Input/Output	16/3 relay type
Motion Detection	supports camera's motion detection*
System Reaction to Alarm Events	buzzer, e-mail, alarm output activation, screen message, recording activation, PTZ
NETWORK	
Network Interface	1 x Ethernet - RJ-45 interface, 10/100/1000 Mbit/s
Network Protocols Support	HTTP, TCP/IP, IPv4, UDP, FTP, DHCP, DNS, DDNS, NTP, UPnP, SMTP
ONVIF Protocol Support	Profile S (ONVIF 2.2 or higher)
PC/MAC Software	Internet Explorer/-
Smartphone Software	IMSeYE (iPhone, Android)
Max. Number of Connections with NVR	10
Bandwidth	128 Mb/s in total to all client workstations
PTZ	
PTZ Functions	pan/tilt/zoom, preset commands*
AUXILIARY INTERFACES	
USB Ports	2 x USB 2.0,
OPERATING SYSTEM	
Operating System	Linux
Operation Mode	triplex
OSD	languages: Polish, English, Russian, others
Control	front panel, IR remote controller (in-set included), PC mouse (in-set included), network
System Diagnostic	automatic control of: HDDs, network, camera connection loss

Security	password protection, IP filtering
INSTALLATION PARAMETERS	
Dimensions (mm)	360 (W) x 48 (H) x 260 (D)
Weight	2 kg
Power Supply	12 VDC (100 ~ 240 VAC/12 VDC PSU in-set included)
Power Consumption	40 W (with 2 HDDs)
Operating Temperature	-10°C ~ 55°C

** Function capability depends on used camera, for details please check the compatibility list. ** For BNC output speed may be lower. *** Available with dual streaming mode.*

