

LCD Monitor NVM-519LCD



LCD 500 *series*

Features

- High resolution color TFT LCD monitors
- Digital 3D filter for picture quality improvement
- Additional matt glass shield protecting LCD matrix against mechanical damage
- Panel type: 19"
- Video input: 2 x BNC (loop-through), HDMI, VGA, S-Video
- Audio input: Jack stereo (loop-through)
- Internal speakers
- Multi-lingual On Screen Display (OSD)
- Power supply: 12 VDC (100 ~ 240 VAC/12 VDC PSU in-set included)

Specifications	Description
Panel Type	19" color TFT LCD Panel
Screen Size (Diagonal)	482.6 (mm)
Viewable Size (mm)	376.3 (H) x 301.1 (V)
CRT Dot Pitch	0.294 x 0.294
Resolution	700 TVL
Viewing Angle (L/R/T/B)	85°/85°/80°/80°
Contrast Ratio	1000:1
Brightness	250 cd/m2
Display Color	16.7 mln
Response Time	5 ms
Video Input	2 x CVBS: BNC connector (loop-through) 1 x VGA 1 x S-Video 1 x HDMI
Audio Input	1 x Jack stereo, (loop-through)
Speaker Output	2 x 1 W
Operation	Multi-lingual On Screen Display (OSD)
Operation System	PAL/NTSC (Auto Scan)
Case	Plastic (black)
Power Supply	12 VDC (100 ~ 240 VAC/12 VDC PSU in-set included)
Power Consumption	42 W
Operating Temperature	0°C ~ 40°C
Dimensions (mm)	423 (H) x 419 (W) x 197 (D)
Weight	5.20 kg
Mounting Standard	VESA 100x100 (brackets available)